



Commercial Swimming Pool Heat Pumps

“
The most cost effective solution to heat your commercial swimming pool 365 days per year.
”

FEATURES & BENEFITS



Water heating up to 40°C



High reliability



Low maintenance



Easy installation



Expert service & support



Environmentally friendly refrigerants

- The heating capacities range between 50 kW and 150 kW.
- Multiple units can be installed together thus catering for any client's needs.
- The EIP-MTC series are equipped with titanium condensers that are suitable for sea-, salt-, and fresh water pools with water temperatures up to 40°C.
- Automatically controlled electronic expansion valves are used to ensure optimal energy efficiency in all climatic conditions.
- Enerflow* heat pumps aim to maximise value for money in terms of life cycle cost.
We focus on quality, reliability and the capitalised operating cost, including the impact of peak demand and electricity consumption tariffs.

Our EIP-MTC series heat pumps are ideally suited for supplying hot water in the following applications:

Olympic size swimming pools
Swimming pools
Spa's

Resorts
Commercial & agricultural heating requirements



www.enerflow.co.za

Contact us:
+27 (0)18 297 0326/7
heatpump@enerflow.co.za

* Enerflow is a proud division of M-Tech Industrial (Pty) Ltd; owned by Royal Bafokeng Holdings

Commercial Swimming Pool Heat Pumps

EIP-MTC series

SPECIFICATIONS

		EIP170MTC	EIP230MTC	EIP330MTC	EIP500MTC
Heating capacity*	<i>kW</i>	50	70	100	150
Coefficient of performance (COP)*		5.0	5.0	5.0	5.1
Water flow	<i>m³/h</i>	6~10	6~12	8~16	15~30
Max outlet water temperature	<i>°C</i>	40			
Rated current*	<i>Amp</i>	19.6	27.2	39.1	57.8
Power supply	<i>V/Ph/Hz</i>	380/3/50			
Rated power input*	<i>kW</i>	10.1	14.0	20.1	29.8
Compressor type		Scroll			
Refrigerant type		R417a			
Noise level at 1 meter distance	<i>dB</i>	≤63	≤64	≤66	≤70
Water connection	<i>mm</i>	50	80	80	100
Cabinet material		Powder coated mild steel			
Dimensions (w x d x h)	<i>mm</i>	880 x 810 x 1070	1480 x 810 x 1100	1950 x 1150 x 1950	3400 x 1150 x 1950
Net weight	<i>kg</i>	192	295	415	535
Water pressure drop	<i>MPa</i>	≤0.4			
Circuit breaker	<i>Amp</i>	30	50	75	100
Waterproof grade type		IPX4			
Heat exchanger		Titanium			



Scan or visit our website (www.enerflow.co.za) to go to our Swimming Pool Heat Pump Calculator and see which heat pump is perfect for your pool.

* Test standard: Ambient temperature of 20/15°C (DB/WB)
Water inlet temperature of 27°C